

# TRANEMO

ADVANCED WORKWEAR



EN ISO 11612  
A1 B1 C1 F1



EN 61482-2  
APC 2  
ELIM: 25,0 cal/cm² ATPV: 25,0 cal/cm²



EN 1149-5



\*\*EN ISO 11611  
CL1 A1



\*\*EN 13034  
type PB(6)



EN ISO 20471  
CL3



EN 343  
3.1



\*EN 342  
(5119+5122)

## 511994 FLAME RETARDANT PARKA + LINING 9128

**Non-Metal, Inherent Flame Retardant quilted parka with taped seams. Comes with sleeveless fibrefur lining 9128 06. Wind and water resistant fabric according to EN 343.**

The parka is ergonomically shaped for work with raised arms. Concealed front zip and double stormflap with press studs. Detachable and adjustable hood. Two loops for communication equipment. Chest pockets with zip. D-ring. Front pockets with flaps. Pockets with fleece lining. Sleeve pocket with flap, hidden D-ring and strap for ID-pocket. Two inside pockets with zip, one for documents/lpad with an integrated mobile phone pocket. Adjustable sleeve width and inside knitted cuffs. Drawcord at the waist and bottom of the parka. HTFR Dobby at the bottom and on the sleeves. Heat sealed reflective stripes for greater comfort. \*The garment is tested in a 3 layer system together with basic underwear. Tranemo recommends underwear 5920/5940 and 5980. \*\*Hood must be used or removed during welding or work with chemicals.



STANDARD  
100  
2176-340  
DT1  
www.oeko-tex.com

**Color:** 94 yellow/navy

**Size:** XS-4XL

**Quality:** 054: Lining, quilted FR, 160+80 g/m²

060: Removable lining - Pile FR, 87% modacrylic / 13% cotton, 320 g/m²

804: Reinforcing fabric, HTFR Dobby, 295 g/m²

943: Mega TX 230IR - 40% modacrylic / 59% viscose / 1% antistatic, PU-laminated, 230 g/m²

